



### SECTION B-B FOR "F-SHAPE" BARRIER

Scale: 1/2"=1'-0"

#### Note:

All #7 and #8 bars shall be placed continuously in the parapet from expansion opening to expansion opening in a simple span bridge and expansion opening to centerline of pier in a multispan bridge. Refer to BR-SS(6.02)-03-27B.

#### Note C:

The constr. jt. between the F-shape parapet and the deck may vary slightly from the joint indicated. For exact details and location of the joint see "Superstructure" Sheet.

## 42' STRAIGHT BACK

APPROVAL	
<i>E. S. Friedman</i>	DIRECTOR
OFFICE OF BRIDGE DEVELOPMENT	
DATE: 6/11/05	
REVISIONS	
SHA	FHWA
10-9-07	.
.	.
.	.
FHWA APPROVAL	.
DATE:	.

STATE OF MARYLAND  
DEPARTMENT OF TRANSPORTATION  
STATE HIGHWAY ADMINISTRATION  
OFFICE OF BRIDGE DEVELOPMENT



SUPPORT BRACKET FOR BRIDGE MOUNTED LIGHT POST  
WITH DUAL CONDUITS AND 42" F-SHAPE PARAPET  
WITH STRAIGHT BACK

STANDARD NO. BR-SS(6.38)-05-248B(L)

SHEET 2 OF 2

SUPER-CONCRETE WORK